




Marshall Multispread has built a strong reputation in Australian agriculture as the number one selling all-purpose fertiliser spreader with over 9000 machines in the field.

Constantly evolving over the past 30 years to keep up with the demands of modern farming, the 14 tonne trailer model is a large capacity spreader for large farming enterprises.



1 900 Series 914T Standard Equipment

With its endless belt feed system the 900 Series has a proven record for long service life and lower torque requirement from the ground drive. The belt is a heavy-duty fabric woven PVC, driven by an industrial grade rubber-lagged pulley and supported by low maintenance stainless steel rollers. To aid the run of the belt tracking rollers are fitted inside the chassis and a crowned front pulley used for quick and easy adjustment. Hydraulic drive spinners with electronic tacho are standard equipment.

2 Ground Feed & Application Rates

A rubber jockey wheel, 20:1 gearbox and combination of 4 sprocket sets gives you an application rate range between 20kg/ha up to 8000kg/ha at any ground speed that suits your paddock conditions. Simple rate charts for popular fertilisers are provided to minimise calibration time.

3 D Type Spinner

The D Type spinner configuration has an overall diameter of 700mm, with four vanes—two short and two long—and a stainless steel fertiliser chute for optimum placement of product onto the spinner discs. Spread widths between passes for fertilisers such as Urea, DAP and Superphosphate are up to 36m and product like Lime & Gypsum to 16m. Minimal adjustment to spinner set-up is required to change from granulated to non granulated spreading. All testing during the development of the D Type spinners was carried out using Australian industry standards.

4 Tyres & Suspension

To reduce crop damage, a special feature of the 914T is the tandem suspension. Manufactured by BPW Germany, the suspension combines a walking beam and self-steering rear swing arms with hydraulic lockout for reversing.

A single axle variant, with 150mm square BPW axle and 750/60 R26 tyres is also available

Optional Equipment

Marshall Multispread MDC App, Roll Tarp, Hopper Screens, 3m Track, Loadcell Weigh System, VRT ready hydraulic feed belt drive.

MODEL	914T
Nominal Load / Volume	14000kg / 12.0m ³
Hopper Feed Type	Endless Belt
Spinner Type / Size	"D" / 700mm
Spinner Drive — Standard	Hydraulic
Spread Rates — Standard	20kg to 8000kg/hectare (with ground drive)
Spread Widths (²)	Granulated up to 36m, non-granulated up to 14m
Speed — Paddock Max	25km/hr (loaded)
Speed — Road Max	80km/hr (empty)
Ground Drive Feed	Jockey wheel / 20:1 Gearbox / 4 speed (²) / Hydraulic Drive (³)
Length — Overall	6260mm
Width — Overall	Single Axle Variant: 3250mm / Tandem Axle Variant : 2900mm
Height — Overall	2800mm
Weight — Nett (approx)	Single Axle Variant: 2800kg / Tandem Axle Variant : 4750kg
Hopper Length	4455mm
Hopper Width	2300mm
Track — Centre of Tyres	Single Axle Variant: 2500mm / Tandem Axle Variant : 2350mm
Axle	Tandem Axle Variant: BPW Tandem / Single Axle Variant: 150mm SQ
Tyres	Single Axle Variant: 750/65 R26 TYRES Tandem Axle Variant: 550/60-22.5 TYRES
	¹ Allowing for wind conditions, speed and fertiliser consistency ² Single Axle Variant ³ Compatible rate controller required

